

ISO 16028 Interchange Flat Face Push Pull

The "Push-Pull" Coupler is built on the A Premier platform, thus allowing "breakaway" capabilities when the coupler is unintentionally left coupled. It is mounted in a clamp fixture, that is designed to be fixed mounted to the structure and when pulled apart in line with the coupler, the PPC Series coupler will breakaway. It is recommended to use the APM series nipple in conjunction with this series for mobile applications.

Applications; refuse compactor/power units, trailer dump connections, snow plow application, agricultural implements.



Body Size	Port Size	Thread Type	Order Code	Part Description
3/8	1/2	NPT	PPC0608FO	Push Pull FF 3/8 x 1/2 SAE
1/2	1/2	NPT	PPC0808FP	Push Pull FF 1/2 x 1/2 NPT
1/2	3/4	SAE	PPC0812FO	Push Pull FF 1/2 x 3/4 SAE
1/2	3/4	NPT	PPC0812FP	Push Pull FF 1/2 x 3/4 NPT
5/8	3/4	SAE	PPC1012FO	Push Pull FF 5/8 x 3/4 SAE
5/8	3/4	NPT	PPC1012FP	Push Pull FF 5/8 x 3/4 NPT
3/4	3/4	NPT	PPC1212FP	Push Pull FF 3/4 x 3/4 NPT
3/4	1	NPT	PPC1216FP	Push Pull FF 3/4 x 1" NPT

(*PPC Series Consists of Coupler and clamp assembly components)



Call us at 847-956-9720, Fax at 847-956-9723, or visit us on the web www.stucchiusa.com